

Colors in OpenGL

- Two color models:
RGB or RGBA (`GLUT_RGB`) and **Color-Index** (`GLUT_INDEX`)
- Both use the Color Cube to hide differences in hardware
 - (R,G,B) triplet where 0.0 = none & 1.0 = full value
- A** or **alpha** in **RGBA** expresses *opacity*
 - 0.0 = fully transparent object and 1.0 = fully opaque object
- `glColor3tv()`, `glColor4tv()`: sets the present drawing color
 - † captures data type of arguments (**b**,i,f,d) **b**: byte
 - v passing arguments by reference rather than by value
- `glClearColor()`: sets the present clear color used by `glClear()`
 - E.g., `glClearColor(1.0,1.0,0.0,1.0)`

Indexed Color

- Overcomes limited-depth pixels
- Use the pixels as indices to a *color-lookup table (palette)*

- $K=M=8$, there are 256 colors in the table

Input	Red	Green	Blue
0	0	0	0
1	$2^m - 1$	0	0
⋮	0	$2^m - 1$	0
⋮	⋮	⋮	⋮
⋮	⋮	⋮	⋮
$2^k - 1$	⋮	⋮	⋮


$\longleftarrow m \text{ bits}$
 $\longleftarrow m \text{ bits}$
 $\longleftarrow m \text{ bits}$

- `glIndexi(element)`
 - selects the present drawing color
- `glutSetColor(int element, GLfloat R, GLfloat G, GLfloat B)`
 - sets the entries in a color table for each window

"White Rectangle"

```
glLineWidth(1.0);
glLineStipple(1, 0xFFFF);
glColor3f(1.0, 0.0, 0.0);
glBegin(GL_LINES);
  glVertex2f(-30, -30);
  glVertex2f(30, -30);
glEnd();
```

```
glLineWidth(1.0);
glLineStipple(1, 0xFFFF);
glColor3f(0.0, 0.0, 1.0);
glBegin(GL_LINES);
  glVertex2f(30, 30);
  glVertex2f(-30, 30);
glEnd();
```



```
glLineWidth(2.0);
glLineStipple(2, 0xCCCC);
glColor3f(0.0, 1.0, 0.0);
glBegin(GL_LINES);
  glVertex2f(30, -30);
  glVertex2f(30, 30);
glEnd();
```

```
glLineWidth(2.0);
glLineStipple(2, 0xCCCC);
glColor3f(1.0, 1.0, 0.0);
glBegin(GL_LINES);
  glVertex2f(-30, 30);
  glVertex2f(-30, -30);
glEnd();
```

Color Interpolation

```
glBegin(GL_LINES);
  glColor3f(1.0, 0.0, 0.0);
  glVertex2f(0.0, 0.0);
  glColor3f(0.0, 0.0, 1.0);
  glVertex2f(0.1, 0.0);
glEnd();
```

- o Vertex color
 - Smooth shading (*GL_SMOOTH*)
 - interpolate the vertex colors
 - Flat shading (*GL_flat*)
 - Use the color of the first vertex
- o Polygons (convex): vertex colors are interpolated for the interior
 - *bilinear interpolation* applied on triangles
- o `glShadeMode(Glenum mode);`
 - *GL_SMOOTH* is the default

Two-Dimensional Viewing

- What objects are displayed is determined by the **viewing** or **clipping rectangle**.
- Clipping window can be specified using the GLU function:

```
void gluOrtho2D(GLdouble left, GLdouble right,
                GLdouble bottom, GLdouble top)
```
- Default is a square 2x2:
 - (left,bottom) = (-1.0, -1.0) and (right, top) = (1.0, 1.0)
- Clipping window is a special case of 3D **viewing volume** defined by the orthographic projection on the plane $z=0$

```
void glOrtho (GLdouble left, GLdouble right,
              GLdouble bottom, GLdouble top,
              GLdouble near, GLdouble far)
```


CS1566, Panos K. Chrysanthis – University of Pittsburgh

25

Coordinate Systems & Matrix Modes

- Object** or **world** coordinates
- Window** coordinates, **screen** or **raster** coordinates
- OpenGL automatically transforms *object* to *window* coordinates
 - `glutInitWindowSize()`, `gluOrtho2D()`
- Two transformation matrices: **model-view** and **projection**

```
glMatrixMode(GL_PROJECTION);
glLoadIdentity();
gluOrtho2D(-1.0,1.0,-1.0,1.0);
glMatrixMode(GL_MODELVIEW);
```



CS1566, Panos K. Chrysanthis – University of Pittsburgh

26

Saving the State



- o Matrix stacks – one for each type
`void glPushMatrix(); void glPopMatrix();`
- o E.g.,
`glMatrixMode(GL_PROJECTION);
glLoadIdentity();
glutPostRedisplay();
glPushMatrix();
ZOOM();
glutPostRedisplay();
glPopMatrix();`
- o Attribute stack – 20 groups of attributes
 - `GL_POLYGON_BIT, GL_LINE_BIT, GL_ALL_ATTRIBUTE_BITS`
`void glPushAttrib(GLbitfield mask);
void glPopAttrib();`

CS1566, Panos K. Chrysanthis – University of Pittsburgh

27

Viewport

- o Viewport allows us to split a window into different parts and restrict drawing within a given part with its own `gluOrtho2D()` properties.
- o This is very useful to maintain proportions (same aspect ratio).
- o `void glViewport(GLint x, GLint y, GLsizei w, GLsizei h);`
 - `w` x `h` pixels in the window with lower-left at (x,y)




CS1566, Panos K. Chrysanthis – University of Pittsburgh

28

Hidden-Surface Removal

- *Visible-surface* or *hidden-surface-removal* algorithms
 - They order the objects so that they are drawn correctly
 - **Z-buffer** algorithm (`GL_DEPTH_TEST`)
`glEnable(GL_DEPTH_TEST);`
 - `glutInitDisplayMode(GLUT_RGB | GLUT_DEPTH);`
 - Allocates **z-buffer** or **depth-buffer**
 - Before redraw the display we need to clear the z-buffer
- ```
void display () {
 glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
 tetrahedron(n);
 glflush();
}
```



CS1566, Panos K. Chrysanthis – University of Pittsburgh

29

## Typical Non-interactive Main Program

```
#include <windows.h>
#include <gl/glut.h>
#include <stdlib.h>

int main(int argc, char** argv) {
 glutInit(&argc,argv);
 glutInitDisplayMode(GLUT_RGB| GLUT_DOUBLE | GLUT_DEPTH);
 glutInitWindowSize(500,500);
 glutInitWindowPosition(0,0);
 glutCreateWindow("My White Rectangle");
 glutDisplayFunc(display);
 Init(); /* set up attributes, set up viewing */
 glutMainLoop();
}
```

CS1566, Panos K. Chrysanthis – University of Pittsburgh

30

## Display Lists (DLs)

- o DLs are a storage mechanism similar to ordinary files,
- o DLs have an *identifier* (int) and a *content* (glNewList, glEndlist)  
glNewlist( ID, execution flag)
  - flag = GL\_COMPILE, GL\_COMPILE\_AND\_EXECUTE
- o E.g.,


```
#define BlueBox 1 /* or some unused integer */
glNewList (BlueBox, GL_COMPILE);
glBegin(GL_POLYGON);
glColor3f(0.0, 0.0, 1.0);
glVertex2f(-1.0,-1.0); glVertex2f(1.0,-1.0);
glVertex2f(1.0, 1.0); glVertex2f(-1.0,1.0);
glEnd();
glEndList();
```

CS1566, Panos K. Chrysanthis – University of Pittsburgh

34

## Display Lists (DLs)

- o Two methods of operations:
  - Immediate mode
  - Retained mode
- o **Display Lists** are a storage mechanism similar to ordinary files.
- o DLs have an *identifier* (int) and a *content* (glNewList, glEndlist)  
glNewlist( ID, execution flag)
  - flag = GL\_COMPILE, GL\_COMPILE\_AND\_EXECUTE



CS1566, Panos K. Chrysanthis – University of Pittsburgh

35

## Example: Blue Box

```
#define BlueBox 1 /* or some unused integer */
glNewList (BlueBox, GL_COMPILE);
glBegin(GL_POLYGON);
 glColor3f(0.0, 0.0, 1.0);
 glVertex2f(-1.0,-1.0); glVertex2f(1.0,-1.0);
 glVertex2f(1.0, 1.0); glVertex2f(-1.0,1.0);
glEnd();
glEndList();
```

## Display Lists (Cont.)

- o A DL is recall (drawn) using `glCallList (int identifier)`:

```
glPushAttrib(GL_ALL_ATTRIB_BITS);
glPushMatrix();
glCallList (BlueBox);
glPopMatrix();
glPopAttrib();
```
- o Additional functions:
  - `glGenLists(number)`  
returns consecutive integers that are unused labels
  - `glCallLists(n, t, p)`  
executes multiple lists, where
    - n: number of lists; p: pointer to the array of lists;
    - t: type of pointer p